

SAFETY-VAC[®]

PATENTED



SAFETY-VAC[®] Model 15G200-DOT

Power System

- Subaru Robin Industrial 9 hp air-cooled engine
- No-spill oil drain
- Full spark arrest
- High torque industrial centrifugal clutch
- V belt drive
- High pressure regenerative blower system
- Vacuum 10 HG, up to 225 CFM (see Service Rating for performance capabilities)

Recovery & Containment

- Four 55-gallon drum vacuum recovery containment system, for a total fluid capacity of 200 gallons
- Automatic system overflow protection
- 2" diameter suction and pressure ports
- 50 feet of 1.5" fuel rated vacuum recovery hose with end-to-end electrical continuity
- 18" surface recovery tool and wand extension with replaceable neoprene squeegee blades and height adjustment for multi-surface operation
- Aluminum quick-connect hose fittings
- Reverse flow evacuation and transfer cycle allows operator to use pressure side blower power to rapidly offload recovered material
- 50' static grounding reel
- 50' capacity live vacuum hose reel

Platform

- Highway-Legal 8' x 5' 3500 gross vehicle weight single axle trailer with lighting
- Stainless steel fasteners

Service Rating

- High speed recovery of low to medium viscosity material from distances up to 50' from unit at depths to eight feet below grade (100' recovery distance at grade level)
- One year warranty from manufacturer

Options

- Lombardini or Yanmar Diesel Engine (Model 15G200-DOT)
- LP engine conversion
- HEPA filters

Advance Compliance Systems LLC.

866.477.4569 / 352.373.7055 / Fx 352.378.2699